

STI PRODUCT CATALOG U.S. Standard & Metric Measurements



It's a System



Not a Machine







About Substrate Technology, Inc.

At STI we are proud to offer products that deliver "real world" solutions for our customers. We are able to do this for a few reasons like hard work, combined experience of over 100 years of contracting, and ISO certified suppliers but mostly we are able to do it because of our founder.

STI was founded in 1995 by William 'Bill' Jones after his some 30 years of floor covering and floor prep experience. As a contractor, Bill realized he was helpless for products that could deliver results productively AND reliably. Sure there were 'systems' on the market but each had their shortcomings and all required some improvising by the end user of the products.

Through numerous trials and subsequent failures Bill put together a system of machinery and diamond tools that can be relied upon to deliver the fastest and most predictable results. There is of course much more to the story of Bills' genius and what has brought STI into its 20th year of business. The point is Bill already made most the mistakes common to our industry and then created systems to prevent these mistakes.

Why does all this matter to you the customer? STI products are turn-key, cutting-edge systems ready to deliver you a solution that is profitable and predictable.

In memory of Bill & Lynn Jones, STI Founders





Service • Support • Success

Substrate Technology Inc 1384 Bungalow Road Morris IL 60450

Office 815-941-4800

www.substratetechnology.com

STI MACHINES

Hertron Chemicals

Slurry Slayer

2807 Prep Master Grinder	1
2420 Prep Master Grinder	2
2418 Prep Master Grinder Propane	3
3030 Prep Master Grinder	4
3038 Prep Master Grinder Propane	5
Prep Master Jr.	6
PM 200 Prep Master Edger	22
IMPACTS AMERICAS MACHINES	
Impacts Shot Blasters	7-8
Shot Blaster Accessories	9
Impacts Dust Collectors	10
DIAMOND SYSTEMS & PREP TOOLS	
Concrete Prep Tools	11-12
Polished Concrete Tools	14-21
FL07 Polishing Pads	13
Turbo Cups	26
EG Prep Tools	26
10 Segment Diamond Tools	26
Carbide Blocks	27
Bush Hammers	27
Dual Seg Tooling	27
Brazed Diamond Cove Wheels	27
EG Daisies	27
Terrazzo Pads	29
Planetary Tooling for Lavina	29
Cash Pads & Cash Dot Pads	30
Spin-1 & Spin-V2 Pads	31
Grout Pans	32
HAND GRINDING TOOLS	
7" Rings, Full Face & Cash Pads	32
5" Razor Pads	32
7" Holders	32
SWING MACHINES & VACS	
Swing Machines	23
Wet Dry Vac	23
VON ARX	
Von Arx Scarifiers & Needle Scalers	24
TOOL HOLDERS	
Tool Plates, Couplers & Adapters	25
Chemicals	

33

STI-2807 Prep/Master® Project sizes up to 2,000 SF/186m²

ITEM NUMBERS: 2807 220V/230V - Item #432807230 2807 380V/480V - Item #432807480

It's a System Not a Machine

Specifications

Motor	7.5 HP - 3 phase 5.5kW
Power Source	220/230 VAC 1 or 3 Phase, 60 Hz 380/480 VAC 3 Phase, 50-60Hz
Power Cord	30 ft./9m (8-4)
Vacuum Hose Connection	3 in./76mm x 25 ft./8m
Weight	743 lbs. 337 kg
Tool RPM	300 RPM to 750 RPM variable
Number of Tools	6
Tools Attachment Style	EG Proprietary Attachment System
Dimensions	57″ L x 28″ W x 51″ H 145 cm x 71 cm x 130 cm
Recommended Vacuum	Dustcom 3003AR (300 CFM) or equivalent

Production Rates

Mastic Removal	375 SF /35 m ² per hr
Thin Set Removal	425 SF /40 m ² per hr
Mil Coatings Removal	225 SF /21 m ² per hr
Polished Concrete	575 SF /53 m ² per hr

P/M Diamond Systems for the <u>STI-2807</u>



STI-2420 Prep/Master® Project sizes up to 5,000 SF/465m²

37 **ITEM NUMBERS:** 2420 220V/230V - Item #432420230 2420 380V/480V - Item #432420480

It's a System



Not a Machine



Specifications

Motor	20 HP - 3 phase 14.7kW
Power Source	220/230 VAC 1 or 3 Phase 60 Hz 380/480 VAC 3 Phase 50-60Hz
Power Cord	30 ft./9m (8-4)
Vacuum Hose Connection	3 in./76mm x 25 ft./8m x Two
Weight	978 lbs. 444 kg
Tool RPM	250RPM (30Hz) to 750RPM (90Hz)
Number of Tools	12
Tools Attachment Style	EG Proprietary Attachment System
Dimensions	75"L x 27"W x 50"H 191 cm x 69 cm x 127 cm
Recommended Vacuum	Red Raider (360CFM) with pre-separator or equivalent

Production Rates

Mastic Removal	475 SF /44 m ² per hr
Thin Set Removal	525 SF /49 m ² per hr
Mil Coatings Removal	325 SF /30 m ² per hr
Polished Concrete	925 SF /86 m ² per hr

P/M Diamond Systems for the STI-2420

To complete your system, continue here. Concrete Prep pg. 12-13

Polished Concrete

pg. 14-19



STI-2418LP Prep/Master® Project sizes up to 5,000 SF/465m²

ITEM NUMBERS: Item #432418001





Specifications

Motor	Kawasaki 18HP LP	
Motor RPM	2,200 - 3,650 RPM	
Vacuum Hose	3 in./76mm x 25 ft./8m x Two	
Connection		
Weight	895 lbs . 406 kg	
Tool RPM	366 RPM to 500 RPM	
Number of Tools	12	
Tools Attachment	EG Proprietary Attachment	
Style	System	
Dimensions	78"L x 27"W x 48"H	
	198 cm x 69 cm x 122 cm	
Recommended Vacuum	Red Raider (360CFM) with pre-separator or equivalent	

Production Rates

Mastic Removal	475 SF /44 m ² per hr
Thin Set Removal	525 SF /49 m ² per hr
Mil Coatings Removal	325 SF /30 m ² per hr
Polished Concrete	925 SF /86 m ² per hr

P/M Diamond Systems for the STI-2418LP

Concrete Terrazzo To complete Prep pg. 12-13 Polishing your system, continue here. Polished pg. 20-21 Concrete pg. 14-19



STI-3030 Prep/Master® Project sizes up to **10,000 SF/929 m²**

ITEM NUMBERS: 2000/230V - Item #433030230 3030 380V/480V - Item #433030480

It's a System





Specifications

Motor	30 HP - 3 phase 22kW	
Power Source	220/230 VAC 1 or 3 Phase 60 Hz 380/480 VAC 3 Phase 50-60Hz	
Power Cord	30 ft./9m (6-4)	
Vacuum Hose	3 in./76mm x 25 ft./8m	
Connection		
Weight	1,320 lbs. 599 kg	
Tool RPM	300 RPM to 750 RPM variable	
Number of Tools	12	
Tools Attachment	EG Proprietary Attachment	
Style	System	
Dimensions	86″L x 30″W x 52″H	
	218cm x 76cm x 132cm	
Recommended Vacuum	Duo Vac (630CFM) with pre-separator or equivalent	

Production Rates

Mastic Removal	600 SF /56 m ² per hr	
Thin Set Removal	600 SF /56 m ² per hr	
Mil Coatings Removal	425 SF / 39 m ² per hr	
Polished Concrete	1,200 SF /111.5 m ² per hr	



P/M Diamond Systems for the STI-3030



STI-3038LP Prep/Master® Project sizes up to **10,000 SF/929 m²**

in II.

It's a System

Not a Machine

ITEM NUMBERS: Item #433038001



Specifications

Motor	Kawasaki 38HP LP	
Motor RPM	2,200 - 3,650 RPM	
Vacuum Hose Connection	3 in./76mm x 25 ft./8m	
Weight	1,084 lbs. 492 kg	
	366 RPM to 500 RPM	
Number of Tools	12	
Tools Attachment Style	EG Proprietary Attachment System	
Dimensions	86"L x 30"W x 48"H 218 cm x 76 cm x 122 cm	
Recommended Vacuum	Duo Vac (630CFM) with pre-separator or equivalent	

Production Rates

Mastic Removal	600 SF /56 m ² per hr
Thin Set Removal	600 SF /56 m ² per hr
Mil Coatings Removal	425 SF / 39 m ² per hr
Polished Concrete	1,200 SF /111.5 m ² per hr

P/M Diamond Systems for the STI-3038LP









FOR POLISHING PROJECTS UP TO 1,000 SF (100 M²) PREP/MASTER[®] JR.

The **Prep/Master**[®] **Jr.** grinder by STI works extremely well in small, hard-to-reach areas that requires a more compact design — perfect for residential garage floors.

This grinder is very aggressive, yet extremely easy to operate due to the smooth operation of the STI rotary gear system. In addition, the low price of the Prep/Master Jr. is very affordable and fits any project budget.

PREP/MASTER JR. FEATURES

- 7.5 HP / 220/240V Single phase / 40 Amps
- Working width: 23 inches (58 cm)
- Heavy head pressure for better performance
- Easy disassembly of machine into two sections for quick transportation (grinding head weight=260 lbs. & handle weight=130 lbs.)
- Screw-in carrying poles for 2- or 3-person lifting
- **Magnetic LED light** that attaches anywhere to illuminate front or behind machine on the cutting path

Disassembles into 2 pieces for easy transportation!



On-board USB Charger & Phone Carrier





S210E SHOTBLASTER



The IMPACTS S210E is the first 110V blaster with the In-Line Separation system. This means better separation of abrasive and dust as well as superior production over similar priced shot blast machines.

Its compact design is ideal for residential contractors, small areas inherent on large projects, and where limited access work areas are in need of a profiled surface.

Specifications		
	STANDARD	METRIC
Blasting Power	3 HP	2.3 KW
Travel Speed	Manual	Manual
Power Supply	110 V/60 Hz, 16A	230 V/50 Hz, 16A
Working Width	8.25 in.	210 mm
Blasting Capacity	430 SF/hr	40m2/hr
Lmin., Lmax. x W	35, 41x x11.6 x	895, 1045 x 295
x Hmin., Hmax.	31, 40 in.	x 795, 1030 mm
Weight	100 lbs	45 kg

S210E-40R SHOTBLASTER



The IMPACTS S210E-40R is a very powerful, but compact and light weight mobile blast machine. The combination of the powerful wheel motor with an optimized separation system and the variable speed drive motor makes the machine very efficient.

S210E-40R is specially developed to achieve a high blasting performance on small and medium-sized areas.

Item #101210004

	Specifications	5
	STANDARD	METRIC
Blasting Power	5.5 HP	4.0 KW
Travel Speed	Up to 59ft/min	Up to 18m/min
Power Supply	220V/1 Phase	400V/50Hz, 1
	60Hz, 30A	Phase 16A
Working Width	8.25 in.	210 mm
Blasting Capacity	861 SF/hr	80m2/hr
Lmin., Lmax. x W	43x x11.8 x	1100 x 300 x
x Hmin., Hmax.	39in.	1000mm
Weight	255 lbs	114 kg

S270E-75R SHOTBLASTER



Item #101270004

The IMPACTS S270E-75R is a very powerful and compact shot blaster for medium horizontal surfaces. A powerful wheel motor with an optimized separation system and variable speed drive motor makes the machine very efficient and easy to operate.

This model is the only "forwardwalking" 10-inch blaster on the market that can also be used as an edger.

Specifications		
	STANDARD	METRIC
Blasting Power	10 HP	4.0 KW
	Variable 0-98	Variable 0-30
Travel Speed	ft/min.	m/min.
Power Supply	230 V/60 Hz, 35A	400 V/50 Hz, 16A
Working Width	10.6 in.	270 mm
Blasting Capacity	1,400 SF/hr	130m2/hr
Lmin., Lmax. x W	49 x 15.25 x	1250 x 390 x
x Hmin., Hmax.	41 in.	1050mm
Weight	365 lbs	166 KG

S125E HAND HELD SHOTBLASTER



The IMPACTS STREAMER S125E is a small hand held, shot blasting machine that is designed for a variety of horizontal and vertical applications.

Its compact, strong design is especially suitable for shot peening of small areas on concrete, screed, and asphalt, as well as small steel surfaces. For vertical application, we recommend using a balancer.

ltem #101125002

S	pecifications	5
	STANDARD	METRIC
Blasting Power	2 HP	1.4 kW
Travel Speed	Manual	Manual
Power Supply	120V/60Hz, 16A	230V/50 Hz, 16A
Working Width	5 in.	125 mm
Blasting Capacity	160 SF/hr. on concrete	15 m ² /hr. on concrete
Length x Width x Height	20 x 7 x 14 in.	500 x 170 x 350 mm
Weight	17.5 lbs.	8 kg





S320E SHOTBLASTER



Item #101320001

As a welcome addition to the IMPACTS Streamer series of equipment, the S320 is a powerhouse in a small package.

At 12.5 inches and 15HP, the S320 Streamer will outblast comparably-sized and priced blasting machines. The most ideal application for this model is the aggressive removal of coatings on large surface preparation projects.

Specifications		
	STANDARD	METRIC
Blasting Power	15 HP	11 KW
	Variable 0-98	Variable 0-30
Travel Speed	ft/min.	m/min.
Power Supply	480 V/60 Hz, 32A	400 V/50 Hz, 32A
Working Width	12.6 in.	320 mm
Blasting Capacity	2,153 SF/hr	200m2/hr
Lmin., Lmax. x W	71 x 18 x 39.5	1800 x 450 x
x Hmin., Hmax.	in.	1000mm
Weight	705 lbs	320 KG

S410E SHOTBLASTER



The S410E Streamer Shot Blaster is a unique machine to the industry because similarly sized machines do not have as much horsepower.

It not only outperforms other blasters for brush blasting, but also blasts more productively in coating removal applications for large projects. Because of the high HP, it also works great on steel deck surface preparation.

Item #101410001

	STANDARD	METRIC
Blasting Power	24 HP	15 KW
	Variable 0-125	Variable 0-38
Travel Speed	ft/min.	m/min.
Power Supply	480 V/50 Hz, 63A	400 V/50 Hz, 63A CEE
Working Width	16 in.	405 mm
Blasting Capacity	2,800 SF/hr	260m2/hr
Lmin., Lmax. x W	73 x 21 x 41	1850 x 540 x
x Hmin., Hmax.	in.	1050mm
Weight	1,076 lbs	488 kg

Specifications

S600E SHOTBLASTER



The S600E Streamer Shot Blaster is the largest in the IMPACTS Americas fleet of mobile shot blasters. It is a two-wheel shot blaster with very high production rates for brush-blasting as well as aggressive removals.

Its 23-inch blasting pattern makes it a reasonably-sized walk-behind blaster that is the most productive for very large project areas.

ltem #101600001

	STANDARD	METRIC
Blasting Power	30 HP	22 KW
	Variable 0-124	Variable 0-38
Travel Speed	ft/min.	m/min.
Power Supply	480 V/50 Hz, 63A	400 V/50 Hz, 63A CEE
Working Width	23.6 in.	600 mm
Blasting Capacity	4,000 SF/hr	400m2/hr
Lmin., Lmax. x W	73 x 29 x 41	1855 x 745 x
x Hmin., Hmax.	in.	1050mm
Weight	1,157 lbs	525 kg

Specifications

S320RD SHOTBLASTER

The S320RD Ride-on propane model is perfect for powerful shot blasting with the added convenience of a seat & steering wheel! At 12.6 inches and 24HP, the S320RD Streamer will out blast comparably-sized and priced blasting machines.



Special Features of the Ride-on Model:

- Contains centrifugal clutch to engage blast wheel control
- Hydraulic pump allows machine to travel forward and reverse, and to raise and lower ride height for transport or for blasting
- On-board Dustcom 3324

- All-in-one "lifting lock" for the dust bin handling
- Electro-pneumatic compressor regulations

Item #101320003

SPECIFICATIONS		
STANDARD	METRIC	
24 HP	17.7 KW	
Variable 0-118	Variable 0-36	
ft/min.	m/min.	
12.6 in.	320 mm	
2,153 SF/hr.	200 m²/hr	
	STANDARD 24 HP Variable 0-118 ft/min. 12.6 in.	



SHOTBLASTER ACCESSORIES

25" MAGNET SWEEPER



Item # 225000124

- Double layer of permanently charged magnets for a greater magnetic field and maximum lifting power
- Sturdy 8-inch steel hub and ball bearing wheels for durability, easy maneuvering, and easy pushing
- 25-inch width covers a large area quicklyRugged Durability
- All moving parts are protected by nylon flange bushings and reduce wear and extend sweeper life
- Rugged 3-piece handle
- Maximum lifting height "" 5 ¾ in. (using a two and a half inch nail)
- Welded design for extra durability and long life
- Stands up on its own when not in use

HANDHELD MAGNETS



Item # 227100071

Handheld Magnet provide an effective and rapid means of lifting small iron and steel parts from stock bins, boxes, kegs, tables, or floor. Smooth, uninterrupted side surfaces allow fast, easy burrowing into loose materials.

A fingertip pull on the release bar drops the load. The standard units have a nylon lower case. A stainless steel lower case is available for hot or very abrasive material.

Pickup capacity: Up to 3 lbs.

WHEEL KITS

- Thick impeller design
- Hard casting metallurgy (manganese)
- Easy to change
- Can also be used in other existing shot blasting machines
- Available for all sized models of IMPACTS shot blasters

ITEM NUMBER	DESCRIPTION
201000001	Wheel Kit for S410 & S320
201000002	Wheel Kit for S270-75R & S210-40R
201000145	Wheel Kit for S210E
201001349	Wheel Kit for S125E

REDUCTION LINERS

- For shot blasting line-stripe prep and removal
- Reduces blasting width of shot blasting machines



2" Liners	MACHINE
201001726	S210E
201001723	S210E-40R
201001811	S270E-75R
4" Liners	MACHINE
201001725	S210E
201001722	S210E-40R
201001810	S270E-75R
6" Liners	MACHINE
201001724	S210E
201001721	S210E-40R
201001809	S270E-75R

STEEL SHOT



S280 - Item # 61003 S330 - Item # 61001

- Tiny steel pellets used as media for shot blasting machines
- For surface prep, cleaning, stripping, descaling, or leveling concrete or metal surfaces
- Creates a light to medium surface profile (shot grit size will determine desired finish)
- Available in 50 lb. bags

DUST COLLECTORS

Dustcom 3324

The dust collector Dustcom 3324 from IMPACTS is an extremely powerful dust collector to be used together with medium size to larger surface preparation equipment. These new innovative details give optimized handling performance on the job site:



• All in one "lifting lock" for the dust bin handling

- Big, ergonomically optimized dust bin
- Removable, changeable dust host connection
- No edges and obstacles outside the frame
- Optimal dimensions, high performance
- Electro-pneumatic compressor regulations

	SPECIFICATIONS	
	STANDARD	METRIC
Power	7.5 HP	5.5 KW
Power Supply	230V or	400V
	480V/60HZ, 16A	50HZ, 16A
Cleaning	Self-Cleaning	Self-Cleaning
Airflow	706 C.F.M.	1200 m³/h
Filter Surface;	6x Filter Cartridges	6x Filter Cartridges
Certifications	355 SF;M	33 m²; M
Dust Bin	28 Gallon	105 Liters
Capacity		
Dust Hose	5" Hose	130 mm Hose
(sold separately)		

Dustcom 4025

The dust collector Dustcom 4025 from IMPACTS is an extremely powerful dust collector to be used together with medium size to larger surface preparation equipment. These new innovative details give optimized handling performance on the job site:



Item # 104000007

•	All-in-one "lifting lock" for the dust bin
	handling

- Capacity: 52 gal. (200 liter)
- Big, ergonomically optimized dust bin
- Removable, changeable dust host connection
- No edges and obstacles outside the frame Optimal dimensions, high performance, low weight
- Can be split into two units
- Lifting locks for easy transportation
- Electro-pneumatic compressor regulations

	SPECIFICATIONS		
	STANDARD	METRIC	
Power	7.5 HP	5.5 KW	
Power Supply	230V or	400V	
	480V/60HZ, 16A	50HZ, 16A	
Cleaning	Self-Cleaning	Self-Cleaning	
Airflow	765 C.F.M.	1300 m³/h	
Filter Surface;	8x Filter Cartridges	8x Filter Cartridges	
Certifications	482 SF;M	44.8 m²; M	
Dust Bin	52 Gallon	200 Liters	
Capacity			
Dust Hose	6" Hose	150 mm Hose	
(sold separately)			



3003AR

The Prep/Master® 3003AR is an industrial vacuum cleaner equipped with large surface cartridge filters which are constantly and frequently cleaned by means of powerful jets of compressed air. Reverse pulse filter cleaning is the most efficient system when vacuuming fine and toxic silica dust, especially when used on continuous duty or to collect large volumes of dust particles.

Power (3 motors)	3 x 1.3HP (4kW)
Power Supply	115V/60Hz, 18A
Depression Rate (Water Lift)	7.4 ft H ₂ 0 (2250mm)
Max. Air Flow Rate	300 CFM (510 m3/h)
Noise level	76 dB (A)
Filter type	Polyester M
Filter surface	29.100 cm ²
Suction Inlet Diameter	2-in. (50 mm)
Capacity	Longopac
Weight	186 lbs. (84 kg)
Dimensions	32 x 26 x 61 in. (80 x 66 x 155 cm)

Item # 104000033

3003AR ACCESSORIES

Wand & Floor Tool

Not a Machine

Longopac

BUD It's a System Not a Machine



Item# 204000277

For quick & easy clean-up

- Sturdy metal materials
- Wand 48" Long, 2" diameter, single bend, chrome body Floor tool with rollers: 18" width
- Gap between floor tool &
- surface is adjustable Brushes & Squeegees are replaceable

Wand	104000030
Floor Tool	104700030
Bristle Refill	104700032
Squeegee Refill	104700034

2" Flexible Hose



Item # 423500252





Concrete Prep

con-crete prep (kän krēt' prep), **n.** surface grinding, removal of mastic, adhesives, thin set, epoxy coatings, surface laitance, and surface correction of rain slabs

CHOOSE YOUR PROFILE OBJECTIVE

Super Fast Removal with_<u>Rough Profile</u>

> STI Concrete Prep

Productive Removal with_<u>Smooth Profile</u> for polishing or installation of floor material

Your Prep/Master[®] achieves the most efficient, effective, and profitable performance by choosing the tools below.

All EG tools on this page are built with the patented EG Quick Change System (Patent 8,192,255).



#000 EG PREP TOOL

- One set of Triple PCD EG Prep Tools consists of 50% righthand tools and 50% left-hand tools
- EG-backed Triple PCD and Diamond Sweep

Item #573330001 Item #573330002

#000R - Right-hand Tool #000L - Left-hand Tool

1 -

#00 EG PREP TOOL

- One set of Double PCD EG Prep Tools consists of 50% righthand tools and 50% left-hand tools
- EG-backed Double PCD and Diamond Sweep

ltem #571603418 ltem #571603412 #00R - Right-hand Tool #00L -Left-hand Tool



#0 PREP TOOL

• 3"/8mm EG-backed Metal Bond Diamond

 Item
 #540242000
 #0S - Soft Bond

 Item
 #540243000
 #0 - Standard Bond

 Item
 #571522325
 #0H - Hard Bond

Number of Diamonds Machine See Needed for Model Page EACH Step

6	STI-2807	2
12	STI-2420	4
12	STI-2418LP	5
12	STI-3030	6
12	STI-3038LP	7
24	STI-4430	8
24	STI-4438LP	9



STI FL-07 Polishing System



Specially formulated for concrete

 ground with metal bond
 diamonds for the absolute best
 finish, OR use the LUX pad as a
 finishing tool for that extra
 "POP!"

Fantastic life of 10,000 SF Works on the Prep/Master®, Planetary Machines, Terrco® Machines, EDCO®, Swing Machines, and Werkmaster®.



#3 - 50 Grit	207000003
#4 - 100 Grit	207000004
5# - 200 Grit	207000005
#6 - 400 Grit	207000006
#7 - 800 Grit	207000007
#8 - 1500 Grit	20700008
#9 - Lux	207000009

4 3/4" Ring Pads

#3 - 50 Grit	207430003
#4 - 100 Grit	207430004
5# - 200 Grit	207430005
#6 - 400 Grit	207430006
#7 - 800 Grit	207430007
#8 - 1500 Grit	207430008
#9 - Lux	207430009









Concrete Polishing




Polished Concrete

pol-ished con-crete (päl'-isht kän-krēt'), **n.** a concrete surface that has been processed using progressively finer grits to produce a reflective condition

CHOOSE YOUR METHOD







Concrete Polishing



STI Classic Polish

sti cla-ssic pol-ish (es-tē-ī klas'-ik päl'-ish), **n.** a grinding and polishing system that is result driven to adequately process and finely polish a concrete floor to its highest possible shine

FOR A HIGH GLOSS SHINE



		_		
SURFACE PROFILE	CLC			
-	CLC#1 - 530400001	Dry Step	achie	Prep/Master [®] ves the most , effective, and
	CLC#3 - 530746003	5	choosing All EGT too built wi	performance by the tools below. Is on this page are th the patented
	CLC#4 - 530752004	Wet Steps		k Change System t 8,192,255).
		U)	Number of Diamonds Needed for EACH Step	Machine Model
20.00	CLC#5 - 530860005			
	5		6	STI-2807
			12	STI-2420
1000 million	CLC#6 - 530870006	Dr	12	STI-2418LP
	6	Dry Steps	12	STI-3030
	CLC#7 - 530880007	;eps	12	STI-3038LP
			24	STI-4430
			24	STI-4438LP




Concrete Polishing


STI PLP Polishing System

sti plp pol•ishing system

(es-tē-ī pē-el-pē päl'-ish-ing), **n.** a grinding and polishing system that is result driven to adequately process and finely polish a concrete floor to its highest possible shine

FOR PREP TO POLISH





PLP

Your Planetary machine achieves the most efficient, effective, and profitable performance by choosing the tools below.

All PLP tools on this page are built with the patented EG Quick Change System (Patent 8,192,255).

See page 22 for STI Planetary Machines.

650mm-750mm Machines		
Steps #1 thru #4 9 tools		
Step #5	12 tools	
Steps #6 thru #9	9 tools	
750mm-800mm Machines		
Steps #1 thru #4	12 tools	
Step #5	18 tools	
Steps #6 thru #9	12 tools	
800mm Machines & Above		
Steps #1 thru #4	12 tools	
Step #5	18 tools	
Steps #6 thru #9	12 tools	
	•	



Terrazzo




te•rra•zzo pol•ish•ing

(te-raz'ō päl'ish-ing), **n.** the grinding and polishing of new epoxy terrazzo from first cut to final polish to produce the highest possible natural shine

FOR PREP TO POLISH





Your Prep/Master® achieves the most efficient, effective, and profitable performance by choosing the tools below.

All EGT tools on this page are built with the patented EG Quick Change System (Patent 8,192,255).



Number of Diamond Needed fo EACH Step

f	
S	Machine
or	Model
0	

6	STI-2807	
12	STI-2420	
12	STI-2418LP	
12	STI-3030	
12	STI-3038LP	
24	STI-4430	
24	STI-4438LP	



STI EDGER





PREP/MASTER PM200

Introducing the STI Edge Grinder and Polisher!

- Works great on Concrete, Terrazzo, Marble, & Granite
- Gets up to 1/8 inch to the edge
- Electronic ignition
- Run wet or dry
- Item # 102000016

Power Source	220/230 VAC 1 or 3 Phase - 50/60Hz 380/480 VAC 3 Phase - 50/60Hz
Power Cord	25ft./8m (6-4)
Vacuum Hose Connection	2in./50mm
Weight	120 lbs./55Kg
Total RPM	1,000 to 2,000 Variable
Tool Attachment Style	EG Patented System
Dimensions	20.5"W x 36-40"H x 36-37"L 52cm W x 91-101cm H x 91-94cm L
Recommended Vacuum	2003P or equivalent

There are three types of tools for the PM200: EG metal bonds, resin dots, and MG pad dots.

Use three tools per set of metal tools, and one each of the remaining pads per set. This system is designed and matched to be used in sequence with no steps being skipped.

PM200 TOOLS & ACCESSORIES



- **3 Oval Segment Tools**
- Metal bond tools
- Size: 3 in.
- EG attachment
- Available in three grits
- Requires three tools per set

Grit	ltem #
------	--------

30	571403030
50	571403050
80	571403080

• Size: 9¹/₄ in.

- Velcro backing
- Resin dots
- Available in three grits

Grit	ltem #
50	349140050
100	349140100
200	349140200



MG Pads

- Size: 91/4 in.
- Use dry only
- Available in four grits

Grit	Item #	
#1	349140400	
#2	349140800	
#3	349141500	
#4	349143000	

Magnetic Plate

• Size: 91/4 in.



- EG slots to hold three
 3-Oval-Segment Tools
- Use magnets to attach Velcro Plate

ltem #820040914

Velcro Plate

- Size: 91/4 in.
- Male Velcro backing for attaching polishing pads



 Three pins to line up with Magnetic Plate

Item #820030914

Substrate Technology, Inc.

HAWK SWING MACHINE



Perfect for the restoration and maintenance of marble, tile, terrazzo, stone, & concrete. Can also be used for standard floor scrubbing, stripping, & polishing applications.

- Planetary steel helical-cut gear drive for superior reliability
- 1.5 HP / 120V
- Dual Electric Motor: 175 & 300 RPM
- 4 gal (15 liter) water tank
- Useful for grinding, polishing, & polishing compound application
- Additional weights available
- Steel brush covers are strong and durable UL / CUL-Approved for safety assurance

17" Swing Machine Item #364590020

20" Swing Machine Item #364590017

SWING MACHINE ACCESSORIES

ITEM NO.	ACCESSORIES FOR 17-INCH or 20-INCH
360001004	4 Gallon Solution Tank
360008045	4.5-inch Weight Post Kit
360028010	Extra 10 lb. Weight - Black
360028025	Extra 25 lb. Weight Hexagonal - Black



Diamond Disc Driver

- Round plate that accommodates six rubber pad holders or prep tools
- High impact polyethylene construction
- Universal mounting arbor for twist-lock attachment

17" Disc Driver Item #ZRML17 20"

Disc Driver Item #ZRML20

17" Pad Driver Item #789217921 20" Pad Driver Item #789220922

Pad Driver

- Round spike plate that accommodates fiber pads for polishing and scrubbing
- · High impact polyethylene construction
- Universal mounting arbor for twist-lock attachment

Hawk 20 Gallon Wet Dry Vac



- 2 HP (1.5kW) 2stage heavy duty bypass motor
- 115V, 60 Hz
- An automatic liquid shut-off prevents motor flooding with foam or solution
- . Comes standard with adjustable frontmount squeegee and dry application accessories
- Kit contains one (1) acid /mildewresistant, non-pleated washable synthetic cloth dust bag
- Quiet operation 78 dB. Meets GS42 standard.

Motor	2HP (1.5kW), 2-stage bypass	
Power Supply	115V/60Hz	
Power Cord	50 ft. 16-3 SJT	
Air Flow	110 CFM	
Water Lift	117 in.	
Tank Capacity 20 gal. (3.78 liters)		
Capacity 17 gal. Wet / 1 Bushel Dry		
dB Rating	78 dB	
Dimensions	22 x 22 x 34 in. (56 x 56 x 86 cm)	
Weight	eight 62 lbs. (28 kg)	



Dry Attachment Kit included



VON ARX PROFILERS, SCARIFIERS, & NEEDLE SCALERS

VON ARX 30 SH WITH HYDRAULIC TRACTION

- Electrical power: 3x 480V / 60Hz
- Motor: 10HP
- Working width: 12"
- Distance to wall: 3.5"
- Dimensions: 53" X 22" X 43"
- Weight: 612 lbs.
- Standard Cutters: Octagonal Cutters or other available

ltem #707199

VON ARX 25 S

- Electrical power: 3x 480V/60Hz
- Motor: 6 HP
- Working width: 10"
- Distance to wall: 2.5"
- Dimensions: 37" X 18" X 46"
- Weight: 220 lbs. /
- Standard Cutters: Pentagonal Cutters or other available

Item #706360



VON ARX DTF 25 SH

- Electrical power: 3x 480V/60Hz or 3x 240V/60Hz
- Motor: 15HP
- Working width: 10"
- Distance to wall: 3"/76mm
- Dimensions: 45" X 19" X 45"
- Weight: 473 lbs.
- Standard Cutters: Diamond blade drum

480V: Item #708701

PREP/MASTER® 45B

- Weight: 10.6 lbs.
- Air consumption: 5.6 cfm
- Needles 3mm: 49 needles
- Air pressure: 100 psi
- Connection thread: R 3/8"
- Acoustic power level: 101 dB

Item #700409

View the Von Arx full product line at vonarx.com.





STITOOL HOLDERS

STI EDGE PLATE

- · Holds all STI tooling & diamonds
- Cuts within $\frac{1}{2}$ inch from edge
- Covers more SF/M² than tool plate
- Eliminates the need for handgrinding to finish edges!
- Fits our most popular Prep/Master® models: 2807 & 3030
- Must use adapter with 3030 Edge Plate to clear gear box lip

Fits Machines	ltem #
Edge Plate for STI-2807	885002807
Edge Plate for STI-3030	885003030
7-3/8" x 1" Adapter for STI-3030	885000738

STI TOOL PLATE

- Holds all STI tooling & diamonds
- Gives the flattest possible floor finish
- Standard for 2420 & 4430
- Also, fits 2807 & 3030



 Fits Machines
 Item #

 2420 & 4430
 884024443

 2807 & 3030
 884028303

EG ADAPTER PLATE – "QUICK CHANGE"

- Attaches to modified STI Tool Plate for after market assembly
- Designed for use with the EG Metal Bond Diamond & EG Adapter-Velcro
- Mounts using 2 bolts (included)

Item #570000014

MORFLEX COUPLER

- Provides flexibility for the tools to follow the contour of the floor
- Good replacement part to have on hand for less downtime

|--|

Size	ltem #	
502 - Standard Flex	880000502	
602 - Standard Flex	880000602	
702 - Rigid for flattest cut	880000702	

E/Z BACKERS

- Bolts to E/Z plug holder
- Velcro backing securely holds diamond pads in place
- Velcro backing allows for fast and easy diamond pad replacement

Aluminum Milled Holder

• Aluminum backer with machined 5/8"-11 arbor

Rubber Holder

• Rubber backer with 5/8"-11 arbor

Baklite Holder

• Hot-pressed rigid baklite with 5/8"-11 arbor

Size	Item #
3"	803000001
4"	804000001
3"	80300002
4"	804000002
3"	80300003
4"	80400003
	3" 4" 3" 4" 3"



EG-QUICK CHANGE ADAPTERS



10 SEGMENT ADAPTER FOR QUICK CHANGE

• Adapter allows for 10S tools to be quickly changed without hardware

Item #570001057

EG ADAPTER - "VELCRO"

- 3 inch diameter
- Female adapter for quick change
- For use with EG Resin Insert

Item #570000031

EG RESIN INSERT

- 3 inch diameter
- Extra support secures tool to velcro head
- Grooved side fits into EG Adapter–Velcro & EG Adapter–Three Hole

Item #570000026



EG-QUICK CHANGE DIAMONDS & TOOLS



EG TURBO CUP



- Quick Change or E/Z Bolt-n
- Use wet or dry
- Used for first cut/closing cuts on new or existing epoxy/portland terrazzo
- · Metal bond diamond for aggressive cutting
- 3"/76mm diameter

Quick Change

Grit	Item #
16	572400160
24	572400240
40	572400400
80	572400800

E/Z Bolt-on



Grit	ltem #	
16	352400160	
24	352400240	
40	352400400	
80	352400800	
	16 24 40	





Color	Grit	Bond	ltem #
Orange	25	Medium	570225300
White	18	Medium	570218200
Black	25	Hard	570225301
Grey	20	Hardest	570220000
Grev (with pin)	20	Hardest	110220000

Grey (with pin) | 20 | Hardest | 110220000



EG SHARK METAL BOND DIAMOND

- 3"/76mm only size available
- Unique diamond design
- Quick removal of thin-mil coatings
- Quick Change
- Use wet or dry

Grit	ltem #
80	57SK80



EG 10S DIAMOND SEGMENTS

- Use for opening steps on uncoated concrete
- · Excellent scratch pattern for old or new concrete
- Use wet or dry
- 3"/76mm diameter / 6 mm thickness
- EG Quick Change attachment

Grit	ltem #
16	571016000
30	571030000
30 "Hard Bond"	571030001
70	571070000
120	571012000



EG PREP TOOLS FOR REMOVAL

- · Fast cutting metal bond tools used to remove epoxy, adhesive, & thin-set
- Great price—variety of styles and grits
- · Not recommended when polishing is provided
- · Color coded for easy identification
- Quick Change attachment

EG-QUICK CHANGE DIAMONDS & TOOLS



CARBIDE BLOCK TOOL WITH QUICK CHANGE ASSEMBLY

STI EG Carbide Cutters For Adhesive Removal

**Carbide cutters Sold Separately

Carbide Cutters attached to a trap style tool with STI EG quick change backing to fit PrepMaster machines. With a PrepMaster rotary style machine, equal number of "right" and "left" rotation tools are needed.

Carpet adhesive can be pretty stingy to remove if it's thick and somewhat fresh. Diamond segments and sand can be used, but carbide slicers are often the better choice.

Like a blade, the carbide edge pushes the soft glue from the surface of the concrete. A diamond segment wants to drag the glue and partially redeposits it.

Yellow glue is latex-based. That means water will soften it and keep friction heat from clogging the blades and slowing production. Black glue is petroleum-based. Water won't do anything to soften the glue, but it will keep the glue from getting hot and turning sticky.

ltem#	Description
573202001	Carbide Block Quick Change Assembly - Right
573202002	Carbide Block Quick Change Assembly - Left
CRBD-SQ	Square Carbide



Item # 249128500

ONLY FOR USE WITH THE PM JR, 28 & 30 PREP MASTERS

- Aggressive profiling tool
- Provides CSP 4 to CSP 5 profile
- Creates slip-resistant finish on concrete, granite, and marble
- Long lasting tool 15,000 SF (1,500 m2)
- Breaks down the surface that standard diamonds can't touch
- Comes with four bolts to attach to any tool plate •

DUAL SEG TOOL FOR REMOVAL

Dual Segment Red Traps For Prep Master Junior

Item # 571930201



30 Grit Soft Bond

- · For Removal and Coatings Prep
- · Fast cutting metal bond tool used to remove epoxy, adhesive, & thin-set
- · Great price
- · Not recommended when polishing is provided
- EG "Quick Change" attachment
- To prep HARD troweled Floors
- Removes Cure & Seal

Brazed Diamond Cove Wheel

- » Radiused edge polishes cove on epoxy and portland based terrazzo
- » Available in 3/4" and 1" Radius

Grit

30

50

70

120

27

- » Available in aggressive & fine grit
- » Water openings in face for even water distribution to work surface

Size	Grit	Item #
3/4"	25/35	950342535
3/4"	80/100	950348010
1"	25/35	950012535
1"	80/100	950018010

Item #

570430000

570450000

570470000

570412000



EG Daisies

- » 3"/76mm Metal Bond diamond
- » Great for polishing preparation on concrete, granite, and terrazzo
- » Sintered diamond technology for smooth cut
- » Wet use only



surface profile) or to mimic a "flamed" profile. These tools are NOT intended, however, to remove any flexible coatings or most epoxies.

STI BUSH HAMMER Concrete Surface Prep

Bush Hammers are long lasting (15,000 SF / 1,500 m2) when used to profile a surface to provide a good bonding surface or anti-slip properties.



The New Terrazzo+ Pads

Why am I paying more for the New Terrazzo+ Diamond Pads?

NEW Terrazzo+ Pad		The Old Pad
Price (each)	\$34.85 USD	\$29.90 USD
Average Life	15,000 SF / 1500 M ²	10,000 SF / 1000 M ²
*Cost per SF/M	¹² \$.028 SF / \$.28 M ²	\$.036 SF / \$.36 M ²

*Assumes a 12-tool Prep/Master[®] machine is being used.

Because the Terrazzo+ is...

- 1. PACKED WITH MORE DIAMONDS: There are <u>70% more diamond and abrasives</u> than the old style Terrazzo pad — <u>37 grams</u> extra to be exact!
- 2. MORE DENSE: The pad was designed using high pressure molding to compress more diamond powder and abrasives into the pad, yet keep the same <u>8mm thickness</u> our customers prefer!
- 3. COVERS MORE SQUARE FOOTAGE: The combination of high-pressure molding and increased quantity of diamond powders makes the Terrazzo+ Pad the longest lasting, fastest cutting resin that STI offers!
- 4. SAVES YOU MONEY!! MORE coverage at a lower cost per SF/M²! (See chart above.)

Unique Features:

- Self Opening Profile
- <u>Unique "Marking interlayer</u>" which changes the color of the slurry when pad is consumed
- <u>Cloth Tab</u> makes it easy to remove the tool from the velcro holder

All this value is packed into a tool that some may call expensive. Except that this tool is a better value than one of our best selling product lines.

Call your STI dealer today at +1.815.941.4800 to find out how to order the new Terrazzo+ Pads you should be using!

With the above to consider, would you still say that you are paying more?

POLISHING PADS



TERRAZZO+ PADS

For wet polishing epoxy- and portland-based terrazzo and stone

- 70% more diamond and abrasives than the old style terrazzo pad
- 3"/76mm diameter / 8mm thickness
- Self Opening Profile
- Unique "marking interlayer" which changes the color of the slurry when pad is consumed
- Cloth tab makes it easy to remove the tool from the velcro holder

Grit	ltem #
50	392200050
100	392200100
200	392200200



STI TERRAZZO PADS

- For wet polishing epoxy- and portland-based terrazzo and stone
- Use as first cut tool on new, unsealed concrete, closing step, & first step of restoration
- Specialized matrix for aggressive cut with fine scratch pattern
- Cloth tab (like the Terrazzo+) makes it easy to remove the tool from the velcro holder
- 3"/76mm diameter: 8 mm
- 4³/₄" & 5³/₄" diameters: 3 mm

No center hole on 3"/76mm size eliminates

collection of debris & spent

Grit	3 inItem#
50	920000050
100	920000100
200	920000200



STI E/Z REDZ PADS

- · For wet polishing epoxy- and portland-based terrazzo & stone
- Used for closing/polishing steps
- 3"/76mm diameter / 8mm thickness
- No center hole eliminates collection of debris and spent diamonds

Grit	ltem #
100	918000100
200	918000200
400	918000400
800	918000800
1500	918001500

PLANETARY TOOLING

SINGLE & DOUBLE ROUND PREP TOOLS



- **Fits Imported** Planetary Machines
- Soft, Medium or Hard Bond
- Available in 16, 30, 60 & 120 Grit



SINGLE ROUND SOFT BOND

903110016		
903110030		
903110060		
903110120		
BOND		
903110116		
903110130		
903110160		
903110120		
HARD BOND		
903110216		
903110230		
903110260		
903110220		

DOUBLE ROUND SOFT BOND

16 Grit	903210016	
30 Grit	903220030	
60 Grit	903210060	
120 Grit	903210120	
MEDIUM BOND		
16 Grit	903210116	
30 Grit	903220130	
60 Grit	903230160	
120 Grit	903240120	
HARD BOND		
16 Grit	903210216	
30 Grit	903220230	
60 Grit	903220260	
120 Grit	903220120	

SINGLE & DOUBLE BAR PREP TOOLS



SINGLE BAR 30 Grit

Soft

Medium

Hard

Planetarv Machines



Fits Imported

Grit

901000030

901001030

901002030

Soft, Medium or Hard Bond

Available in 30



DOUBLE BAR 30 Grit





CASH PADS & Granilux Dots





The CASH Diamond Polishing pads are excellent for Casinos, Convention Centers, Airports, Schools, Hotels, and anywhere else that quick and effective polishing of concrete, terrazzo, marble, and granite is required.

- Excellent for Concrete, Terrazzo, Marble, and Granite surfaces!
- Be green use with water. No chemical is required to achieve shine, but STI recommends PG2 for abrasion resistance, slip resistance, and color enhancement
- Available in 17", 20", & 21" sizes to fit most electric buffers



CASH PADS

17-inch / 432mm	
#1	330170001
#2	330170002
#3	330170003

20-inch / 508mm

#1	330200001
#2	330200002
#3	330200003

21-inch / 533mm

#1	330210001
#2	330210002
#3	330210003

Granilux DOTS

17-inch / 432mm	
50 grit	3 150 70050
100 grit	315070100
200 grit	3 150 70200
400 grit	3 150 70400
800 grit	3 150 70800
1500 grit	3 150 71500
3000 grit	3 150 73000

17-inch / 508mm

50 grit	3 1517 0050
100 grit	315170100
200 grit	315170200
400 grit	315170400
800 grit	315170800
1500 grit	315171500
3000 grit	315173000

21-inch / 533mm

50 grit	3 15 210050
100 grit	315210100
200 grit	315210200
400 grit	315210400
800 grit	315210800
1500 grit	315211500
3000 grit	315213000



The CASH Granilux Dot Pad is a rubber disc with individual resin pads fixed to it and has hook Velcro on the reverse side. The CASH Granilux Dot pads are only to be used with water and NEVER dry.

This tool is used to perform concrete polishing, marble polishing and terrazzo polishing that is smooth, cured and free of any sealer or coating and moderately worn marble or terrazzo floors.

The CASH Granilux Dot System is engineered to be run on a high speed, propane or electric, burnisher, swing machine, or auto-scrubber.







SPIN-1 PADS



The SPIN-1 Pad System polishes concrete faster and better than any other diamond buffing pad on the market and does the work in a fraction of the time when compared to large polishing machines.

- Great for maintaining Polished Concrete!
- Pad life is in excess of 20,000 SF
- Available in 21" & 27" sizes to fit most propane burnishers



21" Pads

Orange	605330400	
Silver	605330800	
Blue	605331500	
Red	605333000	
Black	605339999	
27" Pads		
Orange	606850400	
Silver	606850800	
Blue	606851500	

606853300 606859999

Red

Black

NEW SPIN-V2 PADS



- Diamond-impregnated natural hair pads
- Heavy duty diamond formulation
- For maintenance of polished concrete
- Contact us for custom sizes!!!

- Long life gives the lowest cost per SF, of any DIP pads available anywhere.
- Average cost per SF over the grit range is less than \$0.01 for our 27" HD DIPs when run on a propane powered burnisher to "densify and burnish" new concrete floors or as part of the polishing process on concrete floors.
- Coarser grits may be slightly higher cost and finer grits will generally be considerably lower.
- Our HD DIPs are <u>NOT</u> recommended for use on Marble or Terrazzo floors due to the potential of leaving an "orange peel" surface finish as a result of how aggressively they cut, including our 3000 grit.
- Our Maintenance DIPs should be used on Marble and Terrazzo both when polishing the floor and to maintain the floors gloss and clarity over time.

17" Pads

)
)
)
)
)

21" Pads

200 Grit	900210200
400 Grit	900210400
800 Grit	900210800
1500 Grit	900210100
3000 Grit	900210300
27" Pade	

~ ~ ~	I aus
200 Grit	900270200
400 Grit	900270400

800 Grit	900270800
1500 Grit	900270100
3000 Grit	900270300

HAND GRINDING TOOLS



STI-7" RING-TYPE POLISHING PADS

Works wet or dry

• For use with any variable speed 7" grinder

Grit	ltem#
35	713000035
50	713000050
100	713000100
200	713000200
400	713000400
800	713000800
1500	713001500



STI-7" FULL FACE POLISHING PADS

- Works wet or dry
- For use with any variable speed 7" grinder

Grit	ltem#
35	763000035
50	763000050
100	763000100
200	763000200
400	763000400
800	763000800
1500	763001500



- CASH 7" PADS
- For low-speed hand-polishers
- Great for Marble, concrete or terrazzo
- All the great finish of the CASH system in a smaller size

Grit	ltem#
#1	330070001
#2	330070002
#3	330070003
-	



5" RAZOR PADS, CERAMIC

C1	630050001
C2	63005002
C3	630050003
C4	630050004



STI-7" RUBBER HOLDER

• Rubber backer with velcro to hold 7" Ring Type or Full Face Polishing Pads

Item #80700003

STI-7" RIGID HOLDER

 Baklite backer with velcro to hold 7" Ring Type or Full Face Polishing Pads

Item #80700002

CUP WHEELS



SHARK 7-INCH/180MM CUP WHEEL

- Unique diamond design
- Quick removal of epoxy or mortar
- Fast cut on hard concrete
- 7/8", Non-threaded arbor
- 30 grit

Item #: GS7CW



GROUT PANS



EG GROUT PANS

The rotary action of the Prep/Master[®] pushes the epoxy into the holes from multiple directions to push air out and fill in the holes!

- Fills the pin holes in terrazzo more thoroughly than the conventional way of hand troweling & buffing the epoxy into the holes
- Use on P/M machine or other rotary machines
- Velcro-backed for easy tool change
- Lasts over 10,000SF / 929 $M^{\rm 2}$

Item #640900035

POLISHING COMPOUND, SEALERS, & CLEANERS

PLEASE NOTE:

All chemicals listed on this page are non-stocking items. They will be shipped using ground transport service only. NO air shipments are available for these chemicals.



E/Z POLISH



- · Ready-mixed polishing paste
- · For polishing marble, limestone and terrazzo
- · Aids in water and stain resistance
- · Increases density of surface
- Ideal for maintenance program
- Easy-to-use, non-etching, non-noxious odor
- Easy clean-up
- Available in 10 lb. and 25 lb. containers

Item #380600010 10 lb. Item #380600025 25 lb.



E/Z SEAL

- Transparent, water and oil resistant treatment
- Impregnates and seals marble, terrazzo, concrete, grout joints and all natural stone surfaces
- Formulated to protect interior and exterior surfaces
- · Protects against water and oil
- Special formulation allows for excellent surface breathability
- Coverage ranges from 750 to 1250 sq. ft. per gallon on polished surface
- Porous surfaces may need two applications
- Easy clean-up

Item #380400004 4 gal. Case Item #380400005 5 qal.



E/Z SEAL PLUS

• All the benefits of E/Z Seal with an added enhancer for richer color

Item #380500004 4 gal. Case Item #380500005 5 gal.







- The second of two hardening agents used to ensure a long-lasting surface gloss
- Used also as primary maintenance product in automatic equipment or stand-alone product for swing machine
- Available in three-sized containers

ltem #380310024	4 gal. Case
ltem #380310025	5 gal.
ltem #380310255	55 gal.

ULTIMATE BLACK

- Produces that extra depth and color that is wanted on black stone or high shine on other colors
- Neutral, non-detergent cleaner
- Available in one quart containers


Item #380900001 1 quart

ONE STEP

- A "one component" granite polish
- May be used to polish any color granite
- · Works with regular steel wool pads on a 175 to 300 RPM buffing machine

Item #380119001 1 quart Item #380119006 6-qt. Case





Substrate Technology, Inc. 1384 Bungalow Rd. Morris, Illinois 60450

> +1.815.941.4800 Fax +1.815.941.4600

lt's a System





Service • Support • Success

www.substratetechnology.com